



ExII Strobe Light dSLB 20

**Robust optical signalling device
for use in areas with
explosive atmospheres
in group II and zones 1 and 21**

- ▶ Compact construction
- ▶ Versatile
- ▶ Light intensity up to 15 joule
- ▶ Protection degree IP 66 / 67
- ▶ Explosion protection class
II 2 G Ex d e IIC T5, T6 Gb
II 2 D Ex tb IIIC T95 °C, T80 °C Db

Application

It is often necessary to use optical signals for warning, indicating and signalling purposes in areas with explosive atmospheres.

The ExII strobe light dSLB 20 offers these signalling possibilities. It is designed for continuous operation. The dSLB 20 strobe light is activated by switching on the power supply and is available with various rated voltages. The sturdy housing conforms to protection degree IP 66 / 67 and can be installed both indoors and outdoors.

Design

The ExII strobe light consists of a small flameproof housing of aluminium containing the electronics and a glass cap of hardened borosilicate glass. The terminal enclosure is realised in the explosion protection mode "increased safety".

To built up a signalling combination please use the mounting plate, made by V4A, with integrated junction box from the accessories.


Use on a oil platform

The sturdy housing conforms to protection degree IP 66 / 67 and can be installed both indoors and outdoors.



Technical specifications

Housing	Aluminium, surface lacquered or powder-coated
Colour	Yellow/Blue with borosilicate glass cap and protective cage of stainless steel,
Cap colours	Transparent, red, amber, green, blue
Protection degree	IP 66 / 67 acc. IEC 60529
Protection class	I
Cable gland	1x M20 x 1.5 and 1x blind plug M20 x 1.5 (15 joule version) 1x M20 x 1.5 on the side (5 joule version)
Connection terminals	Power supply: Cross section – 2.5 mm ² single wire 1.5 mm ² fine wire Protective earth – Screw connection with wire protection clamp in connection enclosure max. 2.5 mm ² Equipotential – Screw connection with wire bonding conductor protection clamp outside, cross section max. 4 mm ²
Operating conditions	Indoors and outdoors
Operating position	Any
Operating mode	Continuous
Flash energy	5 joule / 15 joule
Flash frequency	Approx. 60/min. (1 Hz)
Average lifetime	Approx. 5x 10 ⁶ flashes
Temperature range	
Operation	-55 °C to +40 °C (T6) -55 °C to +55 °C (T5)
Expl. protection class	II 2 G Ex d e IIC T5, T6 Gb II 2 D Ex tb IIIC T95 °C, T80 °C Db
Approval	PTB 99 ATEX 1028 IECEX PTB 09. 0062
Weight	Approx. 2 kg



* The full article number is made up by appending the colour code for the coloured cap to the article numbers given below.

transp.	01
red	02
amber	03
green	04
blue	05

Order information

Type	Name	Rated voltage	Flash energy	Current consumption	Art. no.*
dSLB 20	ExII Strobe Light	24 VDC (21 - 53 VDC)	15 Joule	1 A	224 963 ..
dSLB 20	ExII Strobe Light	80 VDC (72 - 132 VDC)	15 Joule	250 mA	224 965 ..
dSLB 20	ExII Strobe Light	115 VAC (103 - 127 VAC)	15 Joule	200 mA	224 966 ..
dSLB 20	ExII Strobe Light	230 VAC (207 - 253 VAC)	15 Joule	200 mA	224 997 ..
dSLB 20	ExII Strobe Light	12 VDC (10 - 14 VDC)	5 Joule	600 mA	224 912 ..
dSLB 20	ExII Strobe Light	24 VDC (21 - 53 VDC)	5 Joule	280 mA	224 913 ..
dSLB 20	ExII Strobe Light	80 VDC (72 - 132 VDC)	5 Joule	90 mA	224 915 ..
dSLB 20	ExII Strobe Light	115 VAC (103 - 127 VAC)	5 Joule	135 mA	224 906 ..
dSLB 20	ExII Strobe Light	230 VAC (207 - 253 VAC)	5 Joule	130 mA	224 907 ..

Accessories

Mounting plate with integrated junction box	229 901 01
---	------------

Subject to change without notice · Printout 02/14



FHF Funke + Huster Fernsig GmbH · P.O. Box 14 01 66 · D-45441 Mülheim an der Ruhr · Gewerbeallee 15-19 · D-45478 Mülheim an der Ruhr
Telephone +49-208-82 68-0 · Fax +49-208-82 68-286 · <http://www.fhf.de> · e-mail: info@fhf.de